



Product information

Water borne silicone free polishing compound designed to quickly and permanently remove sanding scratches from P1500 and finer on all types of surfaces, depending on polishing pad.

Product advantages

- Premium all round polish compound
- One compound solution
- Silicone free



Surfaces

- Clear coats
- Top coats
- Polycarbonate
- Acrylic surfaces
- Solid surfaces
- Gelcoats

Polishing machine

- Rotating 800 – 2000 rpm
- Random orbital polisher 6000-10000 rpm

Polishing pad

- Natural lambswool
- Yellow lambswool pro
- Yellow foam pad
- Orange foam pad

Product properties

Speed:

Polish, gloss:

Work instruction

1. Shake or stir polishing compound before use
2. Do not use too much compound at a time. Use a small amount which is consumed on a focused area - less messing and clean up!
3. Clean thoroughly before and after polishing
4. Work focused on an area of 40x40 cm at a time
5. Polish until a scratch free surface is achieved
6. Keep the pad clean, a dirty pad causes deep swirls and scratches

Technical specifications

Density: 1,05 kg/l
Viscosity: 20,5 Pas
Colour: White
pH: 7 - 8

Storage recommendations

Recommended storage temperature:
5° - 35° C / 41° - 95° F
Keep from freezing