


3M

VHBTM
Tape Since 1980



Maximize possibilities.

The strongest acrylic foam tape in the 3MTM VHBTM Tape portfolio.

3MTM VHBTM Tape Max





Unmatched Performance: 2x Higher Strength

Design and process engineers often face limitations with mechanical fasteners and liquid adhesives. The new 3M™ VHB™ Tape Max Series overcomes these challenges by pushing adhesive technology into a new era of acrylic foam tape performance, with at least 2x higher strength compared to standard 3M™ VHB™ Tapes

When used with the 3M™ VHB™ Tape Max Promoter, this bonding system delivers enhanced strength for applications across a variety of industries, including those previously deemed impossible.

Whether you're manufacturing box trucks, assembling appliances, or constructing buildings, 3M™ VHB™ Tape Max offers maximum strength, design flexibility, and efficiency for your parts and processes.

Exceptional Strength.




The 3M™ VHB™ Tape Max Series delivers bond strength significantly higher than standard 3M™ VHB™ Tapes. This makes it ideal for applications demanding extreme strength, offering at least 2 times greater tensile and overlap shear strength compared to standard 3M™ VHB™ Tapes and similar strength to polyurethane adhesives.

Achieve more with less.



The 3M™ VHB™ Tape Max Series may allow you to achieve high strength bonds using less material compared to standard acrylic foam tapes. This enables more innovative designs and may provide cost savings through enhanced performance and versatility.



Verified Performance.

With up to 470psi in overlap shear strength, the 3M™ VHB™ Tape Max Series is at least 2 times stronger than standard 3M™ VHB™ Tapes.



Streamline production



Increase efficiency



Reduce costs



Bonding system for demanding applications.



3M™ VHB™ Tape Max Promoter* is specifically designed for use with the 3M™ VHB™ Tape Max Series. This adhesion promoter must be applied to each bonding surface to ensure a strong bond between the tape and substrate, enabling optimal performance.



*A water-based adhesion promoter is available from 3M and can be used with the 3M™ VHB™ Tape Max Series. Please contact your local 3M representative if you are interested in learning more.

Watch a demonstration and request a free sample



CLICK

Benefits of the 3M™ VHB™ Tape Max Series include:

- Fast and easy-to-use permanent bonding solution provides high strength and long-term durability.
- Can replace mechanical fasteners (rivets, welding, screws) or liquid adhesives.
- Do more with less. High strength with less total bond area may provide a cost savings compared to standard acrylic foam tapes.
- Allows the use of thinner, lighter weight and dissimilar materials
- Pressure sensitive adhesive bonds on contact to provide immediate handling strength
- No GHS08 health hazard classification for an enhanced working environment



Trust 3M for science-based innovation.

Choose the 3M™ VHB™ Tape Max Series with confidence knowing it was developed based on 3M science and backed by data. It's your go-to solution for the next generation of manufacturing.



Learn more at
<https://engage.3M.com/max>

Ordering information.

Product	Caliper / Size
Max-060GF	0.6 mm (0.025")
Max-110GF	1.1 mm (0.045")
Max-160GF	1.6 mm (0.062")
Max-230GF	2.3 mm (0.090")
Max-Promoter	236 mL (1/2 Pint)
	946 mL (1 Quart)
	3.79 L (1 Gallon)

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action, or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult www.3M.com.



3M Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144-1000 USA

Phone 800-362-3550
Fax 877-369-2923

3M and VHB are trademarks of 3M Company.
© 3M 2025. All rights reserved.