



tesa® 4137

Product Information



Aluminized polyester splicing tape

Product Features

- High reflectivity of both light and heat radiation
- High shear strength
- High ageing resistance

tesa® 4137 is a single-sided product with an aluminized polyester carrier based on an acrylic adhesive system. tesa® 4137 offers excellent heat resistance and easy unwinding characteristics.

Application Fields

- Splicing in high temperature situations, including infrared radiation
- Splicing of plastic coated wallpaper with embossed surfaces
- Splicing of leaders for photo development
- Can be used as sensor tape for proximity detector switches and optical detection switches
- Repairing and fixing in screen printing process

Product Construction

- | | | | |
|--------------------|---------|--------------------|----------|
| • Type of adhesive | acrylic | • Backing material | PET film |
| • Total thickness | 50 µm | | |

Product Properties/Performance Values

- | | |
|--------------------|---------|
| • Tensile strength | 50 N/cm |
|--------------------|---------|



tesa® 4137

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04137>